



Construction and Gauge	Tufted 1/10" cut pile		
Pile Content	100% PES		
Primary Backing	Woven Polypropylene		
Secondary Backing	Standard Fleece		
Pile Weight	2000 gr/m <sup>2</sup>		
Total Weight	2950 gr/m <sup>2</sup>		
Pile Height	11,5 mm		
Total Height	13,5 mm		
Tuft Density	175500/m <sup>2</sup>		
Widths available	4 & 5 metres		
Pattern Repeat	n/a		
Light Fastness	≥ 5		
Sound Insulation	≥ 25 dB		
Tog Rating	1.5		
Fire Class	E <sub>FL</sub> (EN 13501-1)		
Usage	Class 22		



**INSTALLATION :** Securely fix to subfloor with either the tackless gripper method with underlay or on the double stick method. **MAINTENANCE :** Daily vacuum cleaning. Shampoo when necessary in accordance with manufacturer's instructions. While every effort is made to ensure exact colour and design reproduction, we cannot, owing to method of manufacture, guarantee perfect matching. Please note that a sample may not be from the same dye batch as the current production and therefore should be used as a guide and not as an exact colour match. Sharding is a characteristic of all out pile corrects and is not considered to be a manufacturing defect. Sharden max upput from the lat to

Shading is a characteristic of all cut pile carpets and is not considered to be a manufacturing defect. Shades may vary from dye lot to dye lot. Experienced professional installers are essential to ensure correct installation.

## THE COMPANY RESERVES THE RIGHT TO MODIFY SPECIFICATIONS AND ALTER RAW MATERIALS RELATIVE TO IMPROVING PERFORMANCE WITHOUT NOTICE.

A4 Folder Layout



A4Tolder Edyout					
900	905	940	720		
600	925	610	950	780	
780	640	800	700		



## 2 balta










700 – Almond Latte





▲ 610 - Champagne Delight

▲ 720 - Sand Drift








640 - Macadamia Nut



780 - Beach Cave



905 - Ground Mist



🔺 925 – Disco Ball

🔺 950 - Urban Chateau