

Universal 30 - Click
















Technical Data

Click Plank Dimensions

Click plank size	18.3cm x 122cm (7.2" x 48")
Click pack size	2.23m ² - 10 planks

Click Tile Dimensions

Click tile size	30.5cm x 61cm (12" x 24")
Click pack size	2.6m ² - 12 tiles

Name	Standard		Result
Wear Layer Thickness	EN429		0.3m
Total Thickness	EN428		4.5mm
Weight	EN430		7260 g/m ²
Anti-static Performance	EN 1815		< 2.0kV
Impact Sound Insulation	E492-09		IIC=54
Sound Absorption	ISO 717-2		20dB
Thermal Resistance	BS 4745: 2005 (2016) ISO 5085-1: 1989		Tog: 0.38
Dynamic Friction	BS EN 13893: 2002 (2018)		0.0397m ² K/W
Flammability	BS EN 13501-1: 2007 + A1: 2009		E1
Castor Chair Resistance	EN12529		Yes Type W
Slip Resistance	DIN51130		Class R9 DS
Usage Classification	EN685		23 - Heavy Domestic Use 33 - Heavy Commercial Use 42 - Light Industrial Use
Chemical Resistance	EN423		Not affected index
Wear Group	EN660-1		T
Residual Indentation	EN433		0.03mm
Light Stability	EN ISO 105-B02		Degree Level ≥ 6 Method A
Dimensional Stability	EN434		≤ 0.5%
CE Mark	EN14041		EN 14041:2001+AC:2005+AC:2006
Underfloor Heating	EN1264-2		Suitable for underfloor heating. Maximum temperature 27°C
Phthalate Free	Our products are manufactured using both phthalate free and biobased plasticisers except for recycled content		Yes

