

Universal 55 - Click
















Technical Data

Click Plank Dimensions

| | |
|------------------|---------------------------------|
| Click plank size | 18cm x 123cmm (7.09" x 48.43") |
| Click pack size | 2.214m ² - 10 planks |

Click Tile Dimensions

| | |
|-----------------|--------------------------------|
| Click tile size | 30.5cm x 61cm (12" x 24") |
| Click pack size | 2.605m ² - 14 tiles |

| Name | Standard | | Result |
|-------------------------|---|--|---|
| Wear Layer Thickness | EN429 |  | 0.55m |
| Total Thickness | EN428 |  | 5.5mm |
| Weight | EN430 |  | 8100 g/m ² |
| Anti-static Performance | EN 1815 |  | < 2.05kV |
| Impact Sound Insulation | E492-09 |  | IIC=55 |
| Sound Absorption | ISO 717-2 |  | 20dB |
| Thermal Resistance | BS 4745: 2005 (2016) ISO 5085-1: 1989 | | Tog: 0.52 |
| Dynamic Friction | BS EN 13893: 2002 (2018) | | 0.0417m ² K/W |
| Flammability | BS EN 13501-1: 2007 + A1: 2009 |  | B _{fl} - s1 |
| Castor Chair Resistance | EN12529 |  | Yes Type W |
| Slip Resistance | DIN51130 |  | Class R9 DS |
| Usage Classification | EN685 |  | 23 - Heavy Domestic 33 - Heavy Commercial Use 42 - Light Industrial Use |
| Chemical Resistance | EN423 |  | Not affected |
| Wear Group | EN660-1 |  | T |
| Residual Indentation | EN433 |  | 0.05mm |
| Light Stability | EN ISO 105-B02 |  | Degree Level ≥ 6 Method A |
| Dimensional Stability | EN434 |  | ≤ 0.1% |
| CE Mark | EN14041 | | EN 14041:2001+AC:2005+AC:2006 |
| Underfloor Heating | EN1264-2 | | Suitable for underfloor heating. Maximum temperature 27°C |
| Phthalate Free | Our products are manufactured using both phthalate free and biobased plasticisers except for recycled content | | Yes |

