
















# Universal 55 - Herringbone (Click)

## Technical Data

### Herringbone Click Dimensions

Herringbone size	12.7cm x 75cmm (4.92" x 29.5")
Herringbone pack size	1.87m <sup>2</sup> - 20 planks

Name	Standard		Result
Wear Layer Thickness	EN429		0.55m
Total Thickness	EN428		5.5mm
Weight	EN430		8260 g/m <sup>2</sup>
Anti-static Performance	EN 1815		< 2.05kV
Impact Sound Insulation	E492-09		IIC=55
Sound Absorption	ISO 717-2		20dB
Thermal Resistance	BS 4745: 2005 (2016) ISO 5085-1: 1989		Tog: 0.52
Dynamic Friction	BS EN 13893: 2002 (2018)		0.0417m <sup>2</sup> K/W
Flammability	BS EN 13501-1: 2007 + A1: 2009		B <sub>fl</sub> - s1
Castor Chair Resistance	EN12529		Yes Type W
Slip Resistance	DIN51130		Class R9 DS
Usage Classification	EN685		23 - Heavy Domestic 33 - Heavy Commercial Use 42 - Light Industrial Use
Chemical Resistance	EN423		Not affected
Wear Group	EN660-1		T
Residual Indentation	EN433		0.05mm
Light Stability	EN ISO 105-B02		Degree Level ≥ 6 Method A
Dimensional Stability	EN434		≤ 0.1%
CE Mark	EN14041		EN 14041:2001+AC:2005+AC:2006
Underfloor Heating	EN1264-2		Suitable for underfloor heating. Maximum temperature 27°C
Phthalate Free	Our products are manufactured using both phthalate free and biobased plasticisers except for recycled content		Yes

