

Technical Data

Universal - Click

Plank · Herringbone · Tile

Click Plank Dimensions















Click plank size	18cm x 123cm (7.09" x 48.43")
Click pack size	2.214m ² - 10 planks

Click Herringbone Dimensions

Click plank size	12.5cm x 75cm (4.92" x 29.53")
Click pack size	1.88m ² - 20 planks

Click Tile Dimensions

Click tile size	30cm x 60.96cm (12" x 24")
Click pack size	2.78m ² - 15 tiles

Name	Standard		Result
Wear Layer Thickness	EN429		0.55m
Total Thickness	EN428		5.5mm (4:00 SPC + 1.50 IXPE)
Weight	EN430		8.12kg/m ²
Anti-static Performance	EN 1815		< 2.05kV
Impact Sound Insulation	E492-09/ISO1492		TBC
Thermal Resistance	BS 4745: 2005 (2016) ISO 5085-1: 1989		TBC
Dynamic Friction	BS EN 13893: 2002 (2018)		TBC
Flammability	BS EN 13501-1: 2007 + A1: 2009		B _{fl} - s1
Castor Chair Resistance	EN12529		Yes Type W
Slip Resistance	BS EN 13893: 2002		DS R10
Usage Classification	EN685		23 - Heavy Domestic 33 - Heavy Commercial Use
Chemical Resistance	EN423		Not affected
Wear Group	EN660-1		T
Residual Indentation	EN433		0.05mm
Light Stability	EN ISO 105-B02		Degree Level ≤ 6 Method A
Dimensional Stability	EN434		≤ 0.1%
CE Mark	EN14041		Yes
Underfloor Heating	EN1264-2		Suitable for underfloor heating. Maximum temperature 27°C
Phthalate Free	Our products are manufactured using both phthalate free and biobased plasticisers except for recycled content		Yes



myvictoria.co.uk/universal

Issued: 01/08/2024

VICTORIATM
Design Floors