

Technical Data

Universal Design - Dryback

Plank · Fishbone · Parquet

Dryback Plank Dimensions














Dryback plank size 18.4cm x 121.9cm (7.25" x 48")
 Dryback pack size 3.36m² - 15 planks

Dryback Fishbone Dimensions

Dryback plank size 11.43cm x 57.1cm (4.5" x 22.5")
 Dryback pack size 3.397m² - 52 planks

Dryback Parquet Dimensions

Dryback plank size 7.62cm x 30.48cm (3" x 12")
 Dryback pack size 2.323m² - 100 tiles

| Name | Standard | | Result |
|--------------------------|---|--|--|
| Wear Layer Thickness | EN429 |  | 0.55mm |
| Total Thickness | EN428 |  | 2.5mm |
| Weight | EN430 |  | 4.3kg/m ² |
| Anti-static Performance | EN 1815 |  | < 2.0kV |
| Impact Sound Insullation | E492-09/ISO1492 |  | < 3db |
| Thermal Resistance | BS 4745: 2005 (2016) ISO 5085-1: 1989 | | TBC |
| Dynamic Friction | BS EN 13893: 2002 (2018) | | TBC |
| Flammability | BS EN 13501-1: 2007 + A1: 2009 |  | B _{fl} - s1 |
| Castor Chair Resistance | EN12529 |  | Yes Type W |
| Slip Resistance | BS EN 13893: 2002 |  | DS R10 |
| Usage Classification | EN685 |  | 23 - Heavy Domestic 33 - Heavy Commercial Use |
| Chemical Resistance | EN423 |  | Yes |
| Wear Group | EN660-1 |  | T |
| Residual Indentation | EN433 |  | ≤ 0.01mm |
| Light Stability | EN ISO 105-B02 |  | Grade 6 |
| Dimensional Stability | EN434 |  | ≤ 0.25% |
| CE Mark | EN14041 | | Yes |
| Underfloor Heating | EN1264-2 | | Suitable for underfloor heating. Maximum temperature 27°C |
| Phthalate Free | Our products are manufactured using both phthalate free and biobased plasticisers except for recycled content | | Yes |



myvictoria.co.uk/universal

Issued: 01/08/2024

VICTORIATM
Design Floors