

Technical Data

Universal - Dryback

Plank · Herringbone · Tile

Dryback Plank Dimensions














Dryback plank size 18.4cm x 121.9cm (7.25" x 48")
 Dryback pack size 3.36m² - 15 planks

Dryback Herringbone Dimensions

Dryback plank size 12cm x 75cm (4.92" x 29.53")
 Dryback pack size 2.25m² - 24 planks

Dryback Tile Dimensions

Dryback tile size 30.48cm x 60.96cm (12" x 24")
 Dryback pack size 2.78m² - 15 tiles

Name	Standard		Result
Wear Layer Thickness	EN429		0.55m
Total Thickness	EN428		2.5mm
Weight	EN430		4.3kg/m ²
Anti-static Performance	EN 1815		< 2.0kV
Impact Sound Insullation	E492-09/ISO1492		< 3db
Thermal Resistance	BS 4745: 2005 (2016) ISO 5085-1: 1989		TBC
Dynamic Friction	BS EN 13893: 2002 (2018)		TBC
Flammability	BS EN 13501-1: 2007 + A1: 2009		B _{fl} - s1
Castor Chair Resistance	EN12529		Yes Type W
Slip Resistance	BS EN 13893: 2002		DS R10
Usage Classification	EN685		23 - Heavy Domestic 33 - Heavy Commercial Use
Chemical Resistance	EN423		Yes
Wear Group	EN660-1		T
Residual Indentation	EN433		≤ 0.01mm
Light Stability	EN ISO 105-B02		Grade 6
Dimensional Stability	EN434		≤ 0.25%
CE Mark	EN14041		Yes
Underfloor Heating	EN1264-2		Suitable for underfloor heating. Maximum temperature 27°C
Phthalate Free	Our products are manufactured using both phthalate free and biobased plasticisers except for recycled content		Yes



myvictoria.co.uk/universal

Issued: 01/08/2024

VICTORIATM
Design Floors