

Urban Herringbone

Herringbone



15.2 x 61cm (6" x 24")
Pack Size: 42 Planks, 3.90m²

Name		Standard	Result
Wear Layer Thickness		EN429	0.55mm + Polyurethane
Total Thickness		EN428	2.5mm
Weight		EN430	4520 g/m ²
Anti-static Performance		EN 1815	< 2.0kV
Bevelled Edge			Yes
Impact Sound Insulation		E492-09	IIC=63
Maximum Sound Absorption		ISO 717-2	5dB
Thermal Resistance		EN 12667:2001	0.036m ² K/W
Thermal Conductivity		EN 12667:2001	0.076 W/(mK)
Flammability		EN 13501-1	Bfl - s1
Slip Resistance		DIN51130 EN 13893	Class R10 DS
Usage Classification		EN685	23 - Heavy Domestic 33 - Heavy commercial use 42 - Light industrial use
Chemical Resistance		EN423	Yes
Wear Group		EN660-1	T
Residual Indentation		EN433	0.05mm
Castor Chair Resistance		EN425 EN12529	Yes Type W
Light Stability		EN ISO 105-B02	Degree Level ≥ 6 Method A
Dimensional Stability		EN434	≤ 0.12%
Underfloor Heating			Suitable for underfloor heating Maximum temperature 27°C
Phthalate Free	Our products are manufactured using both phthalate free and biobased plasticisers except for recycled content		Yes

