
















# Landscape Tile - Dryback

## Technical Data

### Dryback 12" x 24" Tile Dimensions

Dryback tile size 30.5cm x 61cm (12" x 24")

Dryback pack size 3.34m<sup>2</sup> - 18 planks

Name	Standard		Result
Wear Layer Thickness	EN429		0.7m
Total Thickness	EN428		2.5mm
Weight	EN430		4230 g/m <sup>2</sup>
Anti-static Performance	EN 1815		< 2.0kV
Impact Sound Insulation	E492-09		IIC=63
Sound Absorption	ISO 717-2		5dB
Thermal Resistance	BS 4745: 2005 (2016) ISO 5085-1: 1989		Tog: 0.13
Flammability	BS EN 13501-1: 2007 + A1: 2009		B <sub>fl</sub> - s1
Castor Chair Resistance	EN12529		Yes Type W
Slip Resistance	DIN51130		Class R10
Usage Classification	EN685		23 - Heavy Domestic 33 - Heavy Commercial Use 42 - Light Industrial Use
Chemical Resistance	EN423		Yes
Wear Group	EN660-1		T
Residual Indentation	EN433		0.05mm
Light Stability	EN ISO 105-B02		Degree Level ≥ 6 Method A
Dimensional Stability	EN434		≤ 0.12%
CE Mark	EN14041		EN 14041:2001+AC:2005+AC:2006
Underfloor Heating	EN1264-2		Suitable for underfloor heating. Maximum temperature 27°C
Phthalate Free	Our products are manufactured using both phthalate free and biobased plasticisers except for recycled content		Yes



[myvictoria.co.uk/tech-specs/landscape](http://myvictoria.co.uk/tech-specs/landscape)

**VICTORIA**<sup>TM</sup>

Design Floors

Issued: 15/11/2022